

FastenMaster® TimberLok®

HEAVY DUTY WOOD SCREW

No Predrilling. They Just ZIP Right In!

The design features of this FastenMaster product include:

- No pre-drilling!
Goes through all beams (even up to 8" x 8"). Sharp point penetrates the surface of the wood without any pre-drilling.
- Stronger pull down power.
Thread engages only the lower piece, drawing the top piece down tightly.
- Self countersinking.
Patented tapered underside of the head self countersinks without any added steps.
- Highly corrosion resistant.
Three step coating process resists corrosion better than galvanized fasteners. It's guaranteed.
- Removable.
Stronger shear strength enables the fastener to be removed for temporary applications.
- Free 5/16" driver bit in every box.



For more information or free samples,
call FastenMaster at 800•518•3569.

INSTALLATION PROCEDURE

The FastenMaster TimberLok should be installed using a high torque, 1/2" variable speed drill (at least 18V if cordless). Choose the proper TimberLok length by adding 2" to the depth of the piece being attached and rounding up to the closest available size.

PERFORMANCE DATA

Average Ultimate Single Shear = 2995 lbs.
Average Ultimate Pullout Strength = 1445 lbs.
Comparative Pullout Using:
-Straight Spike = 345 lbs.
-Spiral Shank Spike = 425 lbs.

Pullout tests conducted using pressure treated Southern Yellow Pine

Part Number	Screw Length	Quantity per Pack
FMTLOK04-10	4"	10
FMTLOK06-10	6"	10
FMTLOK08-10	8"	10
FMTLOK10-10	10"	10
FMTLOK212-50	2 1/2"	50
FMTLOK04-50	4"	50
FMTLOK06-50	6"	50
FMTLOK08-50	8"	50
FMTLOK10-50	10"	50
FMTLOK212-500	2 1/2"	500
FMTLOK04-250	4"	250
FMTLOK06-250	6"	250
FMTLOK08-250	8"	250
FMTLOK10-250	10"	250
Thread diameter	.245"	
Shank diameter	.190"	
Head style	hex	
One hex head driver is included in every box.		

BP03005-50M-AVL

PRODUCT FEATURES

5/16" HEX HEAD
(1 FREE DRIVER BIT IN EACH BOX)

PATENTED HEAD STYLE COUNTERSINKS ITSELF DURING INSTALLATION.

3/16" SHANK DIAMETER

MADE OF HEAT TREATED STEEL FOR DRAMATICALLY INCREASED STRENGTH AND DRIVABILITY

ULTRA COATED FOR UNMATCHED CORROSION RESISTANCE

2" OF THREAD WITH 1/4" MAJOR DIAMETER

GIMLET POINT FOR FAST DRILLING

